



FRED SR C

SELF CLEANING, WALL MOUNTED EXTRACTOR

Fred SR 1C
With one 10' capture arm

Fred SR 2C
With two 10' capture arms



This professional grade fume extractor is the industry standard for eliminating smoke, dust and others unbreathable from the air. A 2500 CFM, 5HP blower ensures a high face-velocity across two independently movable capture arms, removing particulate as small as 0.5 micron with our standard MERV 15 rated Nanofiber filter

Our patented Injection Self-Cleaning System (ICS-360) reduces the FRED SR C's total cost of ownership by extending filter life expectancy, improving aggregate filter efficiency, and making routine service faster & easier.

Benefits:

- Automatic Filter Cleaning makes service easy
- Compact, portable and easy to operate
- Capture-at-source for cleaner air
- Complies with OSHA guidelines for controlling weld fumes

Features:

- Flexible 10' externally articulated capture arm
- ICS-360 Injection Self-Cleaning System
- 21" easy-to-service Nanofiber filter (MERV 15)

Options:

- Flexible externally articulated capture arm 6.5', 10', or 13'
- 3.0 HP 1800 CFM High-Static Motor [230/460/575V 3PH]
- Odor Absorption Kits
- Minihelic Gauge
- Spunbond Polyester Filter Cartridge (washable)
- Afterfilter module, with HEPA Filter
- Hood mounted LED light kit





Primary Filters

NANOTECH **XV**

MERV 15 efficient cartridge filter captures particles at the submicron level, and surface-loading technology allows dust to be easily dislodged during cleaning with compressed air.



S-SR-21NF

EFFICIENCY: MERV 15
 FILTER MEDIA: NANOFIBER
 MEDIA AREA: 190 SQ.FT.
 COATING: FIRE RETARDANT
 END CAP: OPEN/CLOSED
 CLEANING METHOD: COMPRESSED AIR
 MAX TEMP: 180° F / 82° C
 FLANGE: NONE

POLYTECH **XI**

MERV 11 efficient cartridge filter captures particles at the submicron level, it provides the highest level of filtration efficiency 99.97% at 0.3 micron.



S-SR-21PT

EFFICIENCY: MERV 11
 FILTER MEDIA: SPUNBOND POLY
 MEDIA AREA: 105 SQ.FT.
 COATING: FIRE RETARDANT
 END CAP: OPEN/CLOSED
 CLEANING METHOD: AIR + WATER WASH
 MAX TEMP: 180° F / 82° C
 FLANGE: NONE

Secondary Filter

HEPA

High strength, high efficiency (99.97% efficient at 0.3 micron) cartridge filter made from 100% spun-bond polyester that lowers costs, by allowing for water-based cleaning of captured contaminants.



S-SR-1009

EFFICIENCY: 99.97% AT 0.3 MICRON
 FILTER MEDIA: HEPA
 MEDIA AREA: 24" x 36" x 5-7/8"
 COATING: NONE
 END CAP: OPEN/CLOSED
 CLEANING METHOD: DISPOSABLE
 MAX TEMP: 175° F / 82° C
 FLANGE: NONE

IMPORTANT : If your equipment was purchased after November 15, 2018, a Replacement Filter Card, featuring filter details and simple instructions to easily order replacement filters, will be located on the filter door.

Dimensions **

Model	Arm Length (ft.)	Arm Diameter (in.)	Dimensions (in.)		
			Width	Height	Length
FRED SR2 C with two externally articulated manual capture arms					
FRED SR 2C	10 (x2)	6 (x2)	32.5	115	33
	13 (x2)	6 (x2)	32.5	128	33

** Product dimensions are based on base-models and may vary depending on selected product features. Please contact us for an accurate shipping quote.

Technical Specifications

Model	Motor (H.P.)	Power					Airflow (CFM)	Cord Length (ft.)	Arm Length (ft.)
		Phase (hz)	@120V (amps)	@230V (amps)	@460V (amps)	@575V (amps)			
FRED SR2 C with two externally articulated manual capture arms									
FRED SR 2C	5.0	3P/60Hz	---	13.0	6.5	5.2	2500	---	10/13

HEAD OFFICE

1200 55th Avenue
Montreal, QC H8T 3J8

DISTRIBUTION CENTERS

CANADA Montreal, QC Toronto, ON
UNITED STATES Trenton, NJ Chicago, IL Reno, NV



An Absolent Group Company

